



MAXIMUM OPERATING TEMP.
200°F
HIGHER TEMPS. AVAILABLE

PART NUMBER	OVERALL LENGTH	NO. OF BANDS	NO. OF PLEATS	AREA OF MEDIA
MT618345	83"	5	45	49ft./2
MT615745	57"	3	45	37ft./2
MT614345	43"	2	45	25ft./2
MT612445	24"	1	45	12.5ft./2
INSERT# 9921				

CUSTOM LENGTHS AVAILABLE AND PLEAT SPACING AVAILABLE TO SUIT INDIVIDUAL REQUIREMENTS

MEDIA OPTIONS

- SPUN BONDED POLYESTER
- METALLIZED POLYESTER
- POLYESTER WITH PTFE MEMBRANE
- CONDUCTIVE ANTI STATIC (WITH GROUND WIRE)

CENTER CORE OPTIONS

- EXPANDED METAL
- PERFORATED METAL
- POLYPROPYLENE

**FAB-TEX
FILTRATION**

1-888-932-2839
www.fabtextilters.com
fabtextiltration@bellnet.ca

PLEATED FILTER ELEMENT

6.25" TOP ACCESS

INSERT STYLE

FITS 6.44" DIA. WHEELABRATOR PLATE
UTILIZES RE-USABLE METAL INSERT